


**KWL EC 2000 D**



**Dimensions KWL EC 2000 D**



Ultra-flat ventilation units with heat recovery for compact and space-saving ceiling installation.

With a wide range of residential, commercial and industrial applications. Independently certified hygiene properties and energy efficiency according to VDI 6022 and the passive house standard. Unit construction and unit components fulfil the general hygiene requirements according to VDI 6022.

Available in various comfort and equipment variants.

**■ Casing**

Double-walled, made of galvanised steel sheet, with 30 mm heat and sound insulation on all sides. The inspection openings for filter replacement are accessible at the bottom of the unit without tools.

Ceiling installation via vibration-damping fastening elements included in the delivery.

**■ Heat exchanger**

Large cross counterflow heat exchanger made of aluminium with heat recovery efficiency of up to 90 %. Dismantling possible in just a few simple steps.

**■ Fans**

Two low-noise high-performance EC fans with backward-curved impellers guarantee maximum energy efficiency. The special control technology enables constant volume control or constant pressure control.

**■ Ducts**

Installation-friendly connection of intake, exhaust, extract and supply air through pipe or duct system NW 400 mm.

**■ Condensate connection**

A separate condensate tray below the heat exchanger facilitates maintenance work on the unit. Drain connectors on the side next to the terminal box. Ball siphon included in delivery. On-site connection to drain pipe.

**■ Air filter**

Standard equipment: Clean intake air supply via ISO ePM<sub>1</sub> 55% filter (F7). The heat exchanger requires a ISO ePM<sub>10</sub> 50% filter (M5) on the extract air side. All filters are pressure-controlled and exchangeable in just a few simple steps.

**■ Summer operation**

Standard equipment with automatic bypass function for maximum comfort.

**■ Heat exchanger anti-icing protection**

An electric preheating element heats the intake air at very low outdoor temperatures. Thus, it prevents the heat exchanger from icing up and guarantees its safe functioning and optimal heat recovery during the entire heating period.

**■ Power control**

The comfort control element with graphic display and user-friendly menu navigation, which is included in the delivery, enables the following functions:

- Control directly via touchscreen.
- Freely definable operating points within the entire range of the performance curve.
- Selection between constant volume control or constant pressure control.
- Demand-oriented ventilation using CO<sub>2</sub>, VOC (mixed gas) or humidity sensor.
- Initial commissioning (automatic determination of the system performance curve).
- Control of external shutters.
- Connection of a fire alarm contact.
- Weekly or daily programme.
- Pressure monitoring of filter contamination.
- Indication of necessary filter replacement, operating status, error messages.
- Different access levels. The ventilation unit is alternatively controllable via ModBus (RS 485, TCP/IP).

**■ Electrical connection**

Easily accessible terminal box on the side of the casing. The isolator/main switch can be controlled from below the unit for maintenance work and it can be locked with a padlock to prevent unauthorised access.

**■ Post-heating**

**Type KWL EC Pro WW**

The integrated warm water heating element guarantees the convenient and energy-efficient post-heating of supply air. The setpoint temperature is simply set in the control element. The hydraulic unit (Type WHSH HE 24 V (0-10 V), accessories) is recommended for controlling the warm water heat exchanger.

**■ Reference**

The ventilation unit design according to VDI 6022 requires the use of VDI 6022-compliant air filters. The use of original replacement air filters is therefore mandatory.

**■ Replacement air filter**

- 1 pc. ISO ePM<sub>10</sub> 50% (M5) ELF-KWL 2000 D/5 VDI No. 04197
- 1 pc. ISO ePM<sub>1</sub> 55% (F7) ELF-KWL 2000 D/7 VDI No. 04204

**■ Other accessories**


Other accessories	Page
KWL peripherals	150 ff.
- Air distribution systems	166 ff.
- Further overview, control lines	170 f.

**Accessory details**

Ventilation grilles, ducts, fittings	
roof outlets	561 ff.
extract air elements	574 ff.

**Performance curve KWL EC 2000 D**

Frequency	Hz	Tot.	125	250	500	1k	2k	4k	8k	
L <sub>WA</sub>	Extract air	dB(A)	59	56	52	48	49	47	45	40
L <sub>WA</sub>	Supply air	dB(A)	77	66	68	67	72	69	69	64
L <sub>PA</sub> at 1 m	Radiation	dB(A)	50	46	42	43	44	38	31	21



**Included in delivery:**  
**Surface comfort control element**  
User-friendly control via self-explanatory graphic elements with clear text directly on the touchscreen. Control line (10 metres) included in delivery, other lengths available (ALB EC-SK, accessories).  
Dim. mm (WxHxD) 115x80x25



**Accessories for Type Pro WW**  
**Hydraulic unit**  
**WHSH HE 24 V (0-10 V)** No. 08318  
Controls the water temperature of the PWW heating element using a three-way valve actuator 24 V (0-10 V) and thus the heat output transferred to the air. Delivered as a complete unit, incl. VL-/RL temperature display, circulating pump and flexible connection hoses.



**Accessories for all types**

**Room sensor – Air quality**

**AIR1/KWL-VOC 0-10V** No. 20250  
**AIR1/KWL-CO2 0-10V** No. 20251  
**AIR1/KWL-FTF 0-10V** No. 20252  
For measuring the CO<sub>2</sub>, mixed gas (VOC) concentration or relative room air humidity. A maximum of one sensor can be connected.  
Dim. mm (W x H x D) 85 x 85 x 27



**Room sensor – Temperature**

**TFR-ALB/KWL** No. 07277  
For measuring the room temperature and controlling the ventilation unit according to the set value. Incl. 20 m control line. Maximum total of one sensor can be connected.  
Dim. mm (W x H x D) 80 x 80 x 25




**Transition piece – Symmetrical**

**KWL-ÜS 2000 D** No. 04208  
From unit flange to round duct systems.

**Flexible connecting sleeve**

**FM 400** No. 01676  
For acoustic decoupling, incl. 2 pcs. hose clamps.



**Duct shutter, motorised**

**RVM 400** No. 02580  
Prevents cold draughts when the unit is at a standstill. Automatic function through fan operation, with mounted spring return motor (outside of air flow). Installation in any position.



**Angle flange ring**

**FR 400** No. 01206  
Made of galvanised steel sheet, for duct connection.

Technical data	KWL EC 2000 D			KWL EC 2000 D, with warm water post-heater		
	Type KWL EC 2000 D Pro	Ref. no. 04175		Type KWL EC 2000 D Pro WW	Ref. no. 04176	
<b>For ceiling installation</b>						
<b>Flow rate at level<sup>1)</sup></b> Supply air/extract air V m <sup>3</sup> /h approx.	1800	1150	720	1800	1150	720
<b>Noise dB(A)<sup>2)</sup></b>						
Supply air L <sub>WA</sub> (sound power)	77	67	57	77	67	57
Extract air L <sub>WA</sub> (sound power)	59	50	40	59	50	40
Radiation L <sub>PA</sub> at 1 m	50	n/a	n/a	50	n/a	n/a
Power consumption fans 2 x W	395	245	150	395	245	150
Voltage/Frequency	3N~, 400 V, 50 Hz			3N~, 400 V, 50 Hz		
Rated current A – Ventilation	6.0 / – / –			6.0 / – / –		
– Preheating	10.0 / 11.0 / 11.0			10.0 / 11.0 / 11.0		
– max. total	16.0 / 11.0 / 11.0			16.0 / 11.0 / 11.0		
Heat output/Postheater kW	–			8.1 (at 60/40 °C) / 7.3 (at 50/40 °C) / 4.6 (at 40/30 °C)		
Electric preheater kW	6.6			6.6		
Summer bypass	automatic			automatic		
Wiring diagram no.	1370			1370		
Temperature operating range	–20 °C to +40 °C			–20 °C to +40 °C		
Connection PWW heating element	–			IG 1/2"		
Weight approx. kg	265			270		

<sup>1)</sup> Values based on operating ranges defined according to PHI (Passive House Institute).

<sup>2)</sup> At 250 Pa.