



GB EC 400



Any installation position and location due to five possible outlet directions.




GB EC 400 T120




For the delivery of contaminated, humid and hot air up to max. 120 °C. Motor located outside of air flow.



Dimensions GB EC 400



Dimensions GB EC 400 T120



Special features of the GB EC T120 series

- Designed for the delivery of contaminated, humid and hot air up to max. 120 °C, e.g. as an extract air fan in commercial kitchens and many process technology applications.
- Motor located outside of air flow.
- Thermally insulated partition between motor and impeller, made of galvanised steel sheet, with 20 mm thick, non-flammable mineral wool.
- Complete motor-impeller unit can be removed without dismantling the system components.
- Inspection cover with handle, easily removable for cleaning and maintenance.
- Condensate tray with condensate drain as standard. Hole provided for rain drain (accessories) for outdoor installation.

Installation

Installation position with condensate drain below. Flexible installation due to three possible centrifugal outlet directions of the outlet fitting. Protected outdoor installation possible with weather protection cover and grille (accessories).

Electrical connection

Standard terminal box (IP54) directly to the commutation electronics.

Special features of the GB EC series

Any installation position and flexible installation due to five possible outlet directions of the outlet fitting. The wall bracket (accessories) must be used for wall installation. Protected outdoor installation possible with weather protection cover and grille (accessories).

Electrical connection

Standard terminal box (IP54) mounted to external cable.

Description for both series

Casing

Self-supporting frame construction made of aluminium hollow profiles. Double-walled, 20 mm thick side panels made of galvanised steel sheet, sound and heat insulated by non-flammable mineral wool lining. Nozzle on inlet side for optimal inflow as well as connectors and flexible connecting sleeve (for the respective max. permissible air flow temperature) for duct connection. Moulded part (square to round) on outlet side for low-loss outflow and flexible connecting sleeve to prevent structure-borne noise transmission. Simple positioning with standard crane hook.

Impeller

Free-running high performance centrifugal impeller made of aluminium, directly driven. Energy-efficient with low noise emission. Dynamically balanced together with the motor in accordance with DIN ISO 21940-11 – quality grade 2.5.

Drive

Energy-saving, speed-controllable EC external rotor motor in protection category IP54 with the highest level of efficiency. Maintenance-free and radio interference-free, ball bearing mounted.


Motor protection

Integrated electronic temperature monitoring system for EC motor and electronics.


Type	Connection Ø	Flow rate free blowing	Rated speed	Case-rad. sound pressure	Power consumption	Current consumption	Wiring diagram	Max. air flow temp.	Weight net aprx.	Universal control system		Speed potentiometer	
										Type	Ref. no.	Type	Ref. no.
mm													
V m³/h													
min⁻¹													
dB(A) in 4m													
kW													
A													
No.													
+ °C													
kg													
Alternating current, 1~, 230 V, 50/60 Hz, EC motor, protection category IP54													
GBW EC 400 A	05817	400	4050	1200	36	0.34	1.52	973	50	43.0	EUR EC ²⁾ 01347	PU 24 ¹⁾ 01736	PA 24 ¹⁾ 01737
GBW EC 400 B	05810	400	5160	1500	37	0.62	2.80	973	50	46.0	EUR EC ²⁾ 01347	PU 24 ¹⁾ 01736	PA 24 ¹⁾ 01737
T120 Alternating current, 1~, 230 V, 50/60 Hz, EC motor, protection category IP54													
GBW EC 400 T120	06453	400	4730	1320	43	0.43	1.80	1223.1	120	60.0	EUR EC ²⁾ 01347	PU 10 ¹⁾ 01734	PA 10 ¹⁾ 01735
T120 Three-phase current, 3~, 400 V, 50/60 Hz, EC motor, protection category IP54													
GBD EC 400 T120	06454	400	5410	1500	46	0.62	1,20	1214.1	120	60.0	EUR EC ²⁾ 01347	PU 10 ¹⁾ 01734	PA 10 ¹⁾ 01735

1) Multiple EC fans can normally be connected. 2) Alternative electronic diff. pressure/temperature controller (EDR/ETR, No. 01437/01438) or three level speed switch (SU/SA, No. 04266/04267).


Performance curves GBW EC 400 A




Performance curves GBW EC 400 B



Performance curves GBW EC 400 T120



Performance curves GBD EC 400 T120



■ Power control

Continuously variable speed control with internal (delivery) or external potentiometer or continuously variable speed regulation with universal control system (see table). Performance levels are shown in the performance curve as an example.

■ Noise

The total level and range are specified above the performance diagram for:

- Case-radiated sound power
- Inlet side sound power
- Outlet side sound power

The case-radiated noise as sound pressure at 4 m (free field conditions) is also specified in the type table and the table below the performance curve.

■ Accessories for both series

Vibration dampers for indoor installation. 1 set = 4 pcs.
SDD-U Ref. no. 05627

Wall bracket for wall installation.
GB-WK 400 Ref. no. 05626

Weather protection grille for outlet-side coverage.
GB-WSG 400 Ref. no. 05639

Weather protection cover for protected outdoor installation.
GB-WSD 400 Ref. no. 05748

■ Special accessories

for GB EC series
Condensate tray with drain connectors (central) for duct/hose connection.
GB-KW 400 Ref. no. 05644
(a condensate tray with condensate drain is included in delivery for GB EC T120).

for GB EC T120 series
Rain drain for outdoor installation (Hole in casing base already provided).
GB-RA Ref. no. 09418

■ References Page

Universal control system, electronic controllers, Speed potentiometer	613 ff.
---	---------