



- Ventilation grille LGR Rectangular, with adjustable blades.
- For covering rectangular air inlet and outlet openings, preferably in flat rectangular ducts.
- Centrally adjustable blades allow the individual modification of the passage area and thus the alignment and adjustment of the volume flow.
- Corrosion-resistant design made of galvanised steel and white stove enamelling.
- Delivery incl. installation frame which provides universal installation possibilities. In case of installation in thin-walled ducts, attachment with four screws.



- Ventilation grille QVK Square, with adjustable blades.
- Can be used to cover supply and extract air openings with square cross-section.
- Centrally adjustable blades allow the individual modification of the passage area and thus the alignment and adjustment of the volume flow.
- Corrosion-resistant design made of galvanised steel and white stove enamelling.
- Delivery incl. plaster frame.
  Therefore suitable for flush-mounted wall installation and screw attachment without a frame.



- Ventilation grille G fixed
  For attachment to ventilation openings in ceilings and walls.
- ☐ Made of high-quality, UV-resistant and break-resistant plastic.
- ☐ Flat design. Simple attachment with dowels.
- Sight screening with appropriate installation.



- Ventilation grille G fixed For covering and insertion in round ventilation openings.
- Made of high-quality, break-resistant plastic. Corrosion-resistant and thus ideally suitable for external and internal installation.
- Simple installation in round ducts due to rear conical plug-in connectors. Foam strip included in delivery for press-fit attachment. Fixed installation possible with four holes in the corners. When the grille is permanently mounted, the grille insert can be easily removed and replaced for cleaning.

## Product range


Туре	Ref. no.	Colour	Compatible w/ fan NS mm
G 200	00255	White	200
G 250	00256	White	250/280
G 315	00798	White	315
G 355	00799	White	355
G 400	00800	White	400
G 500	00801	Li. grey	450/500

## Product range

Type R		Compatible with rect. duct opening mm i.L.
LGR 250/150	00927	228 x 128
LGR 450/150	00928	428 x 128
LGR 350/230	00929	328 x 208
LGR 450/230	00930	428 x 208

## Product range

Туре	Ref. no.	Applicable up to fan NS mm
QVK 200	00791	200
QVK 250	00792	250
QVK 315	00793	315
QVK 355	00794	355
QVK 400	00795	400




## Product range

Туре	Ref. no.	NW in mm	Colour	VE
G 100	00796	90/100	White	1
G 100 B	00782	90/100	Brown	1
G 100 VE*	00828	90/100	White	12
G 160	00893	150/160	White	1

\* Cost-effective bulk pack.


Dim. in mm - see table




Туре	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$		n mm b	Wgt. kg
LGR 250/150	160	250	150	0.6
LGR 450/150	320	450	150	1.0
LGR 350/230	430	350	230	1.2
LGR 450/230	575	450	230	1.5



Туре	Free cross- section cm <sup>2</sup>	Dim. in mm B	Wgt. kg	
<b>QVK 200</b>	320	□ 250	0.8	
<b>QVK 250</b>	490	□ 300	1.0	
<b>QVK 315</b>	680	□ 350	1.3	
<b>QVK 355</b>	920	□ 400	1.8	
OVK 400	1190	T 450	3.2	



Туре		Dimensions in mm				Wgt.
	$\square$ A	В	С	D	Ø	kg
G 200	287	210	210	39	5.2	0.7
G 250	337	240	240	39	5.2	0.9
G 315	340	300	300	22	5.2	0.4
G 355	390	350	350	22	5.2	0.4
G 400	440	400	400	22	5.2	0.6
G 500	540	490	465	30	5.2	1.8



Type	Dimensions in mm				Wgt.	
	$\square$ b	$\square$ B	С	S	ØD	kg
G 100	90	140	28	15	100	0.8
G 160	130	190	40	24	150	0.3