



■ **T-pieces**
made of steel sheet, galvanised.

Type	Ref. no.	Nominal Ø mm
TS 100	01479	100
TS 125	05720	125
TS 160	05805	160



■ **Duct connector**
made of steel sheet, galvanised.

Type	Ref. no.	Nominal Ø mm
RVB 80	05993	80
RVB 100	05994	100
RVB 125	05995	125
RVB 160	05987	160
RVB 200	05997	200
RVB 250	05998	250
RVB 315	05999	315
RVB 355	05991	355
RVB 400	05992	400



■ **Duct reductions**
made of galvanised steel sheet or plastic*.

Type	Ref. no.	Nominal mm	Reduced Ø mm
RZ 100/80*	05223	100	80
RZ 125/100*	05222	125	100
RZ 160/125	05729	160	125
RZ 160/150*	07684	160	150
RZ 200/160	05710	200	160



■ **Hose clips**
Metal band with turnbuckle.
Delivered as a packaging unit with 10 pcs.

Type	Ref. no.	Nom. Ø mm
SCH 80/100	05722	80 – 115
SCH 125/160	05723	115 – 165
SCH 200	05724	165 – 215
SCH 250	05725	215 – 265
SCH 315/355	05727	265 – 375
SCH 400	05728	375 – 425




Helioflex ALF
Fully flexible ventilation duct
Universally applicable for various industrial, commercial and residential building applications (e.g. for general air and air-conditioning technology, extract air ducts from extraction hoods, tumble dryers etc.).

- **Special features**
- Eliminates storage, shipping and volume problems.
 - One box approx. 60 cm in length contains 10 m duct.
 - Optimal in handling and processing.
 - Smallest poss. bending radius.
 - Superelastic, optionally rebendable, no material fatigue and no leakage.
 - Self-extinguishing in case of fire.

- **Design**
- Two-layer polyester film, aluminium-coated.
 - Integrated spring steel spiral for reinforcement.
 - No toxic gas release in case of fire.
 - Operating temp. from –20 to +100 °C.
 - Max. operating pressure: 2500 Pa
 - Max. permissible flow velocity: 20 m/s.

Type	Ref. no.	Nom. Ø mm	Internal Ø mm	Weight for 10 m	Shipping unit
ALF 80	05711	80	80	1.2	10 m
ALF 100	05712	100	102	1.4	10 m
ALF 125	05713	125	127	1.9	10 m
ALF 160	05757	160	160	2.5	10 m
ALF 200	05715	200	203	4.8	10 m
ALF 250	05716	250	254	5.3	10 m
ALF 315	05717	315	315	9.3	10 m
ALF 355	05758	355	356	9.7	10 m
ALF 400	05759	400	406	11.2	10 m



- **Fitting F**
For square shutters for transition to round.
- Application: This can be used for attaching shutters in series VK, RVK, EVK and RAG directly to round ducts or fan connectors (series HQ/HW).
 - Installation: The four holes in the corners correspond to the attachment points on the shutters. The round connector can be placed on the fan casing and attached using self-tapping screws.
 - Material: Galvanised steel sheet.

■ **Product range**

Type	Ref. no.	Shutter NS cm	Dim. in mm		
			A	B	ØD.i.L.
F 200	00804	20	240	55	210
F 250	00805	25	290	55	259
F 315	00807	30	340	55	324
F 355	00808	35	390	55	364
F 400	00809	40	440	55	409
F 450	00810	45	490	55	460
F 500	00811	50	540	55	510
F 560/630	00257	63	685	55	570
F 630 ¹⁾	00813	63	685	55	640
F 630 ²⁾	00826	63	685	55	634
F 710 ¹⁾	00824	71	785	55	717
F 710 ³⁾	00825	71	785	55	707

1) For Type HQ. 2) For Type HW.
3) For Type AVD DK.



■ **Connectors AS**
With square flange plate (102 x 102 mm) and round connector (50 mm long), made of plastic. For attaching ducts (ND 100) on flat surfaces.

AS 100	Ref. no. 05224
--------	----------------