


MB EC 315



Dimensions MB EC 315



Dim. in mm

Connection: Ø 355 mm

■ **Casing**

Double-walled, made of galvanised steel sheet. Sound insulated by lining with 30 mm thick mineral wool insulation boards. Duct connectors on inlet side and outlet side, with rubber lip seal, adapted to standard diameter. Motor-impeller unit fully retractable for inspection and cleaning, suspended on stable hinges. Comes with condensate drain and drip protection with the doors open as standard. Includes mounting rails made of galvanised steel with screwed-on vibration dampers for easy installation.

■ **Impeller**

Backward curved, free-running high performance centrifugal impeller made of aluminium, mounted directly on motor shaft. High efficiency, low noise. Dynamically balanced in accordance with DIN ISO 21940-11 – quality grade 6.3.

■ **Drive**

Energy-saving, speed-controllable EC internal rotor motor (MBD EC 315 A EC with external rotor motor) in protection category IP55 with the highest level of efficiency, located outside of the air flow. Maintenance-free and radio interference-free, ball bearing mounted.

■ **Electrical connection**

Standard terminal box (IP55) on outside of motor, mounted to external cable for 1~ type.

■ **Motor protection**

Integrated electronic temperature monitoring system for EC motor and electronics. If the maximum permissible motor temperature is exceeded, 3~ types will automatically reduce the speed which then returns back to the originally set value after cooling down. The motors in 1~ types will be deactivated if the maximum permissible temperature is exceeded.

■ **Power control**

Continuously variable speed control with potentiometer or continuously variable speed control with universal control system (see table). Performance levels are shown in the performance curve as an example. MBD EC 315 A: Stepless speed control with internal push buttons (scope of delivery).

■ **Noise**

The total level and range are specified above the performance diagram for:


- ☐ Case-radiated sound power
- ☐ Inlet side sound power
- ☐ Outlet side sound power

The case-radiated noise as sound pressure at 1 m (free field conditions) is also specified in the type table and the table below the performance curve.


Type	Ref. no.	Connection	Flow rate free blowing	Rated speed	Case-rad. sound pressure	Power con- sumption	Current consump- tion	Wiring diagram	Max. air flow temp.	Weight net appr.	Universal control system		Speed potentiometer				
		Ø									flush-mounted		surf.-mounted				
											mm	V m³/h	min ⁻¹	dB(A) at 1 m	kW	A	No.
Alternating current, 1~, 230 V, 50/60 Hz, EC motor, protection category IP55																	
MBW EC 315	05852	355	2150	1500	50	0.20	0.85	985	100	43.0	EUR EC ¹⁾²⁾ 01347	PU 10 ¹⁾	01734	PA 10 ¹⁾	01735		
Three-phase current, 3~, 400 V, 50/60 Hz, EC motor, protection category IP55																	
MBD EC 315 A	05851	355	3500	2500	59	0.83	1.30	1582	120	44.0	EUR EC ¹⁾²⁾ 01347	PU 10 ¹⁾	01734	PA 10 ¹⁾	01735		
MBD EC 315 B	05846	355	4200	3000	65	1.38	2.20	988	120	50.0	EUR EC ¹⁾²⁾ 01347	PU 10 ¹⁾	01734	PA 10 ¹⁾	01735		

1) Multiple EC fans can normally be connected. 2) Alternative electronic diff. pressure/temperature controller (EDR/ETR, No. 01437/01438) or three level speed switch (SU/SA, No. 04266/04267).04266/04267), see accessories.


Performance curves MBW EC 315



Performance curves MBD EC 315 A



Performance curves MBD EC 315 B



Accessories

Wall bracket

Bracket for wall installation, made of galvanised steel sheet.

MB-WK EC315 Ref. no. 05527



Weather protection cover

For protected outdoor coverage. Made of galvanised steel sheet, mounted above motor.

MB-WSD EC315 No. 01865



Flexible connecting sleeve

Includes 2 hose clamps; for installation between fan and duct system. Prevents structure-borne noise transmission and bridges installation tolerances.

– Max. temperature +70 °C

FM 355 Ref. no. 01675

– Max. temperature +120 °C

FM 355 T120 Ref. no. 01658



Universal control system

For continuously variable control or regulation of single phase and three-phase EC fans with a setpoint input of 0–10 V DC.

EUR EC Ref. no. 01347



Speed potentiometer

For direct control/setpoint setting for EC fans with potentiometer input.

PU 10 Ref. no. 01734

For flush-mounting.

PA 10 Ref. no. 01735

For surface-mounting.



Five-step speed switch

SA-5 10 Ref. no. 40229

Five-step switch for surface mounting. For five-step control of EC fans or frequency inverters. Steps from 2 to 10 V can be set via off-set. Protection class IP54.

Accessory details Page

Universal control system, electronic controller, speed potentiometer 617 ff.

