

- Isolator switch/main switch
- 3-pole with auxiliary contact



RHS 3+1 Ref. no. 01594
 "0" position can be locked with a padlock. In accordance with DIN EN 60204 p.1/VDE 0113-1. Plastic casing for surface-mounted installation. 3-pole with auxiliary contact, for single-speed and speed-controlled fans.

Technical data
 Voltage 400 V, 3~, 50 Hz
 Load capacity
 – Main contact AC 3 / 5.5 kW 12 A ind.
 – Aux. contact AC 3 / 2.2 kW 4 A ind.
 Protection category IP54
 Dim. mm W 101 x H 126 x D 104
 Weight approx. 0.35 kg
 Wiring diagram no. 505.2

- Isolator switch/main switch
- 6-pole with 2 aux. contacts



RHS 6+2 Ref. no. 01595
 "0" position can be locked with a padlock. In accordance with DIN EN 60204 p.1/VDE 0113-1. Plastic casing for surface-mounted installation. 6-pole with 2 auxiliary contacts, for all pole-changing fans.

Technical data
 Voltage 400 V, 3~, 50/60 Hz
 Load capacity AC 3 / 5.5 kW
 Protection category IP65
 Dim. mm W 90,5 x H 90,5 x D 140
 Net weight approx. 0.41 kg
 Wiring diagram no. 1440

- Pole changing switch
- for separate winding PGWA
- for Dahlander winding PDA

Surface-mounted



Surface-mounted operating switch for pole-changing fans.

Type	Ref. no.	Load capacity	No.
For separate winding			
PGWA 25	40791	AC 3/5.5 kW 25 A	1554
PGWA 40	40792	AC 3/15 kW 40 A	1554
For Dahlander winding			
PDA 25	40789	AC 3/5.5 kW 25 A	1552
PDA 40	40790	AC 3/15 kW 40 A	1553

Technical data for all types
 Voltage 400 V, 3~, 50/60 Hz
 Protection category IP65

Type	Dim. mm			Weight aprx. kg
	B	H	T	
PGWA 25	90.5	90.5	105	0.31
PGWA 40	115	115	130	0.61
PDA 25	90.5	90.5	140	0.42
PDA 40	115	115	158	0.69

- Reverser and pole changing switch
- for separate winding PGWA
- for Dahlander winding PDA

Surface-mounted



PWGW Ref. no. 01281
For separate winding

PWDA Ref. no. 01282
For Dahlander winding

For speed switching and changing the air flow direction of individual pole-changing fans.
 Grey plastic casing.

Technical data for all types
 Voltage 400 V, 3~, 50/60 Hz
 Load capacity AC 3 / 11 kW
 Protection category IP65
 Dim. mm W 115 x H 115 x D 160
 Net weight approx. 0.59 kg (PWGW)
 0.61 kg (PWDA)
 Wiring diagram no. 1434 (PWGW)
 1435 (PWDA)

- Speed switch DS 2
- for two-speed γ/Δ switchable three-phase current fans
- for two level alternating current fans (SlimVent, RR)



DS 2 Ref. no. 01351
 Speed switch and on/off switch for two-speed three-phase current fans in γ/Δ connection. Grey plastic casing for surface-mounting.

DS 2/2 Ref. no. 01267
 Speed switch and on/off switch for two-speed 1~ fans, Types RR and SlimVent SVR, SVS.

Technical data for all types
 Voltage 400 V, 3~, 50/60 Hz
 Load capacity AC 3 / 5.5 kW / 25 A
 Protection category IP65
 Type DS 2:
 Dim. mm W 90,5 x H 90,5 x D 140
 Net weight approx. 0.42 kg
 Wiring diagram no. 1437
 Type DS 2/2:
 Dim. mm W 90,5 x H 90,5 x D 105
 Net weight approx. 0.29 kg
 Wiring diagram no. 1442