


ALB EC 60/35 WW



Dimensions ALB EC 60/35 WW



Dim. in mm

- **Application /Function**
Pleasant indoor climate through the addition of external fresh air which is filtered and automatically heated to the specified temperature.

Operational unit for connection to rectangular duct systems. Suitable for a wide range of commercial applications.

- **Description/Scope of delivery**

The air filter, fan and warm water heater are integrated in a compact flat casing which is thermally and acoustically insulated. The unit is delivered ready for connection and includes an external control unit for controlling the unit, as well as a connection cable (10 metres). Air quality, humidity and temperature sensors (see Accessories) can be connected to the electronics in the terminal box to control the specified setpoints. In order to prevent frost damage to the unit, a shutter (see Accessories) is essential.

- **Casing**

Robust construction made of coated steel sheet, double-walled with 30 mm thick mineral wool lining. The cover is easy to open with screw caps and hinge for cleaning purposes. Rectangular duct connectors on inlet side and outlet side, adapted to standard rectangular duct dimensions. No thermal bridges, smooth surface for easy cleaning.

- **Filter**

The large filter for long cleaning intervals is freely accessible by opening the casing cover. Standard version ISO Coarse 90% (G4). Alternatively, filters with higher classifications ISO ePM₁₀ 70% (M5) or ISO ePM₁ 50% (F7) (see accessories) can be used. The volume output reduction must be taken into account. Periodic filter inspection /cleaning is required. A filter monitoring system is integrated. The filters comply with VDI 6022.

- **Fan**

The volume flow rate switching is continuously variable with the control unit. Low-noise and high performance centrifugal fan made of galvanised steel sheet. Motor/impeller unit freely accessible for servicing. Drive through energy-saving, speed-control-lable EC motor with the highest level of efficiency. Maintenance-free, with lifetime lubricated ball bearings.

- **Heating element**

Air heater with AL blades and staggered copper pipes heat the intake air to the specified setpoint temperature. Control through connection of a hydraulic unit (accessories) via the integrated control board. The setpoint and the temperature measured by the room sensor (accessories) are constantly compared.

A frost protection circuit is integrated as standard. Max. operating pressure 1.6 MPa. Water connection pipes with external thread.

- **Electrical connection**

Spacious terminal box in IP20 on outside of casing.

- **Motor protection**

Deactivation when overheating is imminent. Automatic reactivation after cool down.

- **Noise**

The type table shows the radiated noise and outlet side air noise as sound pressure at 1 m (free field conditions). If necessary, a cross talk silencer (see Accessories) must be integrated in the duct system on site. The radiated noise as sound pressure level at 1 m (free field conditions) is additionally stated in the type table as well as in the table below the performance curve.

- **Control**

The control element is included in the delivery and offers the following functions:

- Operation with different volume flows.
- Weekly and seasonal timer.
- Temperature control (using room sensor, accessories).
- Frost protection.
- Control of hydraulic unit (accessories) to control the WW heating element. Specification of min./max. temperature.
- Control of an EC extract air fan.

- Display of ambient temperature, fan control and filter contamination.

- **Other inputs and outputs:**

- Emergency switch contact.
- Boost switch contact.
- External switch.
- Input for air quality or humidity sensor.
- Input for room temperature sensor.
- Output for shutter control.




Control element with connection cable (10 m) included in delivery. Dimensions mm (W x H x D) 115 x 80 x 25

Type	Ref. no.	Flow rate* free blowing	Max. speed	Sound pressure level		Voltage 50/60 Hz	Power consump.		Current consump. max. tot.	Wiring diagram	Maximum intake temp.	Weight net aprx.
				Case-radiation	Air noise outlet side		Motor	Heating				
		V m³/h (max.)	min-1	dB(A) at 1m	dB(A) at 1m	Volt	kW	kW	A	No.	+°C	kg
ALB EC 60/35 WW	06536	4070	2650	63	80	400, 3N~	1.03	—	1.90	1371	40	70

* Volume reduction by approx. 5 % when using the filter ISO ePM₁₀ 50% (M5), by approx. 15 % when using the filter ISO ePM₁ 50% (F7).

Performance curves ALB EC 60/35 WW



Accessories

Hydraulic unit

WHSHE 24 V (0-10 V) No. 08318

For controlling the heat output of the warm water heating element in combination with room/duct sensors. Includes flow/return temperature display, pump, actuator, mixer valve, gravity brake, thermal cladding and flexible connection hoses.



Replacement and pollen filter

– ISO Coarse 90 % (G4)

ELF-ALB 280/4/60/35 G4 No. 03649

– Filter class ISO ePM₁₀ 70 % (M5)

ELF-ALB 280/4/60/35 M5 No. 03650

– Filter class ISO ePM₁ 50 % (F7)

ELF-ALB 280/4/60/35 F7 No. 03654

Large cassette filter for long cleaning intervals. Unit = 3 pcs.



Room sensor – Air quality

AIR1/KWL-CO2 0-10V No. 20251

AIR1/KWL-FTF 0-10V No. 20252

For measuring the CO₂ concentration or relative room humidity. Maximum total of one sensor can be connected.

Dim. mm (W x H x D) 85 x 85 x 27



Room sensor – Temperature

TFR-ALB/KWL Ref. no. 07277

For measuring the room temperature and controlling the ventilation unit according to the setpoint.

Dim. mm (W x H x D) 80 x 80 x 25



Connection cable

– 20 metres long

ALB EC-SK 20 Ref. no. 06816

– 40 metres long


ALB EC-SK 40 Ref. no. 06817

Attach between ALB and control element as well as between ALB and TFR-ALB/KWL.

Transition piece – Symmetrical

ALB-ÜS 280/4/60/35 No. 07516

From unit flange to round duct systems.



Duct shutter, motorised

RVM 355 Ref. no. 02579

Prevents cold draughts when the unit is at a standstill. Automatic function through fan operation, with mounted spring return motor. Installation in any position, closing force adjustable corresponding to fan power and installation position.



Flexible connecting sleeve

FM 355 Ref. no. 01675

For acoustic decoupling, incl. 2 pcs. hose clamps.



Angle flange ring

FR 355 Ref. no. 01205

Made of galvanised steel sheet, for duct connection.



Flexible connector

VS 60/30 Ref. no. 05697

Flexible rectangular duct connector with double-sided flange frame.



Counter flange

GF 60/30 Ref. no. 06922

Flange frame made of galvanised steel sheet for connection to the rectangular duct.



Multi-leaf damper for rectangular duct installation

JVK 60/30 Ref. no. 06913

Frame casing with double-sided flanges, positioning mechanism outside of air flow. Electrical drive see STM, Accessories.



Fitting

FSK 60/30 Ref. no. 00834

For cost-effective integration of rectangular duct fans in round duct systems with Ø 315 mm.



Rectangular duct silencer

KSD 60/30-35 Ref. no. 08730

For outlet and inlet side insertion in the rectangular duct system.



Other accessories

Other accessories	Page
Silencers	498 ff.
Hydraulic unit details	496 ff.
Flexible ventilation ducts, ventilation grilles, fittings, shutters	565 ff.
Supply air disc valves	588 f.

Reference

The integration of air filters ELF-ALB 60/35 F7 (ISO ePM₁ 50 % (F7)) in intake air systems fulfils the requirements of VDI 6022.

Reference

Reference	Page
Planning information	14 ff.