

HQ 315



Also available in version:



HW 315



HS 315




HRF 315




Also available in version:




Dimensions HQ 315




Dimensions HW 315



Dimensions HS 315



Dimensions HRF 315



Description for all types

■ Casing

Made of galvanised steel sheet, types HQ and HW have additional two layer lacquer coating in papyrus white. Explosion-proof types have no lacquer coating.

■ Impeller

High performance characteristics with profiled blades made of plastic, dynamically balanced. Different for explosion-proof types.

■ Drive

Closed die-cast aluminium casing. Prot. cat. IP55. Ball bearing mounted. Maintenance-free and radio interference-free. Winding with moisture proof coating. See type table for max. air flow temperature. Different for explosion-proof types.

■ Motor protection

All types (except for 3~ explosion-proof, see page 190) are equipped with thermal contacts. These should be wired with the motor protection circuit breaker (see type table) for effective motor protection.

For types H.W 315/6 and all 1~ explosion-proof fans, the thermal contacts are wired in series with the winding, automatic deactivation and reactivation after cool down.

■ Electrical connection

Standard terminal box (IP55) on back of motor. Additionally on outside of duct for HRF types. Different for explosion-proof types.

■ Protection grille

Made of powder-coated steel for HQ/HW (HQ Ex galvanised), and plastic for HS. In accordance with DIN EN ISO 13857.

■ Power control

The voltage-controllable types are identified in the "Current consumption max. with control" column with a value which must be observed when determining the controller (see speed controller column). Possible assignments of frequency inverters to fans are shown in the type table. The flow rates are shown in the performance diagram.

■ Reverse operation

All types are reversible using a reverser switch. Performance reduction of approx. 1/3 in abnormal flow direction.

■ Installation

Installation possible in any position, but be aware of any condensate drain holes depending on usage.

■ Dimensions

Pole-changeable and explosion-proof types may differ from the above information.

■ Noise levels

See performance diagram. The sound power and sound pressure at 4 m distance under free field conditions are specified for the average operating point on the inlet/outlet side. See page 14 f for noise emissions and room acoustics. Different for explosion-proof types.


Speed	Flow rate free-blowing	Power consump.	Current consump.		Wiring diagram	Max. air flow temp.		Weight net appr.	Design type								Dim. B Motor protrusion in mm
			at rated voltage	max. with control		at rated voltage	with control		HQ incl. protection grille	Ref. no.	HW incl. protection grille	Ref. no.	HS incl. protection grille	Ref. no.	HRF	Ref. no.	
min ⁻¹	V m ³ /h	W	A	A	No.	+ °C	+ °C	kg									
Single-phase alternating current, 230 Volt, 50 Hz, Capacitor motor, protection category IP55																	
920	1330	33	0.25	0.35	317 ¹⁾	60	40	9.0	HQW 315/6	01105	—	—	HSW 315/6	00142	HRFW 315/6 ¹⁾	00202	—
1390	2080	104	0.45	0.47	475 ¹⁾	60	40	8.0	HQW 315/4	01106	HW 315/4	01004	HSW 315/4	00143	HRFW 315/4 ²⁾	00203	—
Three-phase current, 400 Volt, 50 Hz, Squirrel-cage rotor, protection category IP55																	
950	1370	68	0.27	0.32	469	60	40	9.0	HQD 315/6	01117	—	—	—	—	—	—	—
1330	1960	84	0.24	0.26	469	60	40	9.0	HQD 315/4	01118	HWD 315/4	01019	HSD 315/4	00158	HRFD 315/4	00223	—
2790	4000	550	2.16	—	776	60	—	11.0	HQD 315/2	01119	—	—	—	—	HRFD 315/2	00224	50
Pole-changeable, 2 speeds, three-phase current, Dahlander winding, 400 Volt, 50 Hz, protection category IP55																	
720/1445	980/2060	49/115	0.20/0.43	—	472	60	—	12.0	—	—	—	—	HSD 315/8/4	00346	HRFD 315/8/4	00391	—
1310/2835	2100/4050	170/750	0.8/1.86	—	777	60	—	13.0	HQD 315/4/2	01131	—	—	HSD 315/4/2	00348	HRFD 315/4/2	00393	85
Explosion-proof, II 2G Ex h IIB T3 Gb, Motor Ex d, alternating current 230 Volt, 50 Hz, protection category IP55																	
1370	2070	60*	1.25*	—	757	40	—	13.0	HQW 315/4 Ex	00442	—	—	—	—	HRFW 315/4 Ex	00439	—
Explosion-proof, II 2G Ex h IIB + H₂ T3 Gb, Motor Ex e, three-phase current 400 Volt, 50 Hz, protection category IP55																	
925	1400	250*	0.80*	—	470	40	—	23.0	HQD 315/6 Ex	01098	—	—	—	—	—	—	—
1355	2140	120*	0.37*	—	470	40	—	14.0	HQD 315/4 Ex	01147	—	—	—	—	HRFD 315/4 Ex	00473	—
2900	4130	550*	1.31*	—	470	40	—	8.0	HQD 315/2 Ex	01148	—	—	—	—	HRFD 315/2 Ex	00474	—

* Motor ratings, Ex see information on page 20. protection circuit breaker.


¹⁾ Type HRFW../6: Connection according to wiring diagram no. 963. ²⁾ Type HRFW../4: Connection according to wiring diagram no. 965.

³⁾ Incl. motor


Performance curves 315/2




Performance curves 315/4




Performance curves 315/6



Performance curve 315/8



Accessories for HRF 315 Description see page 278 ff.



a) Shutter, motorised see Accessories product pages.

b) See below for types for explosion-proof fans.

Frequency inverter with integrated sine filter		Transformer speed controller 5-step, pole changing switch		Electronic speed controller, continuously variable flush-m./surface-m.		Motor protection circuit breaker for connecting built-in thermal contacts		Reverser switch	
Type	Ref. no.	Type	Ref. no.	Type	Ref. no.	Type	Ref. no.	Type	Ref. no.
—	—	TSW 0.3	03608	ESU 1/ESA 1	00236/00238	—	—	WS	01271
—	—	MWS 1.5⁴⁾	01947	ESU 1/ESA 1	00236/00238	MW	01579	WS	01271
FU-BS 2.5⁴⁾	05459	RDS 1³⁾	01314	—	—	MD	05849	WS	01271
FU-BS 2.5⁴⁾	05459	RDS 1³⁾	01314	—	—	MD	05849	WS	01271
FU-BS 2.5⁴⁾	05459	—	—	—	—	MD	05849	WS	01271
Pole changing switch									
—	—	PDA 12⁵⁾	05081	—	—	M 3⁴⁾	01293	PWDA	01282
—	—	PDA 12⁵⁾	05081	—	—	M 3⁴⁾	01293	PWDA	01282
—	—	not permitted	not permitted	not permitted	not permitted	—	—	—	—
—	—	not permitted	not permitted	not permitted	not permitted	—	—	—	—
—	—	not permitted	not permitted	not permitted	not permitted	—	—	—	—
—	—	not permitted	not permitted	not permitted	not permitted	—	—	—	—

⁴⁾ Incl. speed pole changing switch. ⁵⁾ Flush-m. version see Switch product page.

Other accessories Page

^{b)} Access. for expl.-proof fans

Flanged flexible connector
STS 315 Ex Ref. no. 02503

Flexible connecting sleeve
FM 315 Ex Ref. no. 01690

Extension sleeve for HS
VH 315 Ref. no. 01344

Cylindrical pipe section, galvanised steel, 15 cm long.

Filter and silencers 483 ff.

Shutters and ventilation grilles 563 ff.

Speed controllers, controllers and switches 601 ff.