

Smoke detector

RMR Ref. no. 04984
Smoke detector according to EN 54-7, incl. detector base for the automatic triggering of EVS for smoke detection. Operating voltage 9-33 V DC. Power consum. rest/alarm 30 µA/20 mA. Protection class IP40. Dim. mm Ø 100 x H 44.



Fire service switch

FWS 2 Ref. no. 08255
Fire service switch with LED display for connection to RDA / TSA. Operating voltage 18 – 30 V DC. Power consum. rest/alarm 2/20 mA. Protection class IP44. Dim. mm 125 x 70.

Accessory:
Locking cylinder FWS ZY
Ref. no. 82331.



Push-button alarm

DKM Ref. no. 04985
Push-button alarm in limit value technology for manual triggering of EVS by button. Includes reset button and LED indicator for operating state. Operating voltage 20-30 V DC. Protection class IP40. Colour RAL 2011. Dim. mm W 125 x H 125 x D 36



Safety pressure switch

DDB Ref. no. 82062
Safety pressure switch for monitoring differential pressures and protection against impermissibly high differential pressure, e.g. in RDA/TSA DDK and TSA. Pressure meas. range 20 to 300 Pa. Capacity switch contact 1.0 (0,4) A, 250 VAC. Protection class IP54. Dim. mm approx. 58 x 104 mm. Installation Wall and ceiling installation.



Signaltransmitters

BLH Ref. no. 04983
BL Ref. no. 08216
WH Ref. no. 08217
Flash light siren (BLH), flash light (BL) and siren (WH) as 24 Volt signal transmitters, incl. base. Casing made from impact-resistant plastic, for ceiling and wall installation. Protection class IP65. Dim. mm Ø 93



Differential pressure sensor

DDR Ref. no. 82061
Differential pressure sensor in two-wire technology with durable capacitive sensor element. Operating voltage 18 to 30 V DC. Meas. range -100 to +100 Pa. Casing protection class IP65. Dim. mm 106 x 83 x 41 mm. Casing material Polyamide PA 6.6.

Accessories: Connection adapter
DDR ADPT No. 37525



Duct smoke detector

RMK Ref. no. 04982
Duct smoke detector, incl. inlet duct for early detection of fire gases in the outside air inlet at flow speeds of 1 – 20 m/s. Operating current 16-28 V DC. Power consum. rest/alarm 22/11 mA. Protection class IP54. Relay contact potential-free break contact. Dim. mm L 250 x W 135 x H 100.

