

- Isolator switch RS
- 3 pole with auxiliary contact



RS 3+1 7.5 Ref. no. 06387
Plastic casing for surface-mounting. Locking options in position "O OFF" and position "I ON".

Technical data
Voltage 400 V, 3~, 50/60 Hz
Operating current 20 A
Capacity AC-23 B, 7,5 kW
Prot. category IP65
Protect. class II
Actuation Rotary actuator
Temperature range -25 °C to +60 °C
Weight approx. 0.3 kg
Casing UV and weather resistant
Wiring diagram no. 1088

- 6 pole with auxiliary contact



RS 6+1
Plastic casing for surface-mounting. Locking options in position "O OFF" and position "I ON".

Technical data
Voltage 400 V, 3~, 50/60 Hz
Prot. category IP65
Protect. class II
Actuation Rotary actuator
Locking options "O OFF" and "I ON"
Temperature range -25 °C to +60 °C
Casing UV and weather resistant
Wiring diagram no. 1088

*RS 6+1 55: -25 °C to +40 °C.

Type	Ref. no.	Capacity			Cable entry main contact	Size cable entry
For Dahlander winding or ∇/Δ start-up						
RS 6+1 7.5	06388	20 A	AC-23 B	7.5 kW	4 pcs	M20
RS 6+1 11	06389	25 A	AC-23 B	11 kW	4 pcs	M25
RS 6+1 15	06390	32 A	AC-23 B	15 kW	4 pcs	M25
RS 6+1 22	06391	50 A	AC-23 B	22 kW	4 pcs	M40/32/25
RS 6+1 37	06392	80 A	AC-23 B	37 kW	4 pcs	M40/50
RS 6+1 45	06393	125 A	AC-23 B	45 kW	4 pcs	M50
RS 6+1 55	06394	125 A	AC-23 B	55 kW	4 pcs	M40/50

- Smoke exhaust isolator switch B RS
- 6 pole with auxiliary contact



B RS
EN 12101-3 certified smoke spill inspection switch in temperature-time classification F400. Metal casing for surface mounting. Locking options in position "O OFF" and position "I ON".

Technical data
Voltage 400 V, 3~, 50/60 Hz
Prot. category IP65
Protect. class II
Color RAL 7035
Actuation Rotary actuator
Temperature-Time classification F400
Casing UV and weather resistant
Wiring diagram no. 1394

Type	Ref. no.	Capacity			Cable inlets for main connectors	Dimensions in mm (WxHxD)
B RS 6+1 11 F400	40088	25 A	AC-23 B	11 kW	4 pieces, M25	150 x 150 x 132
B RS 6+1 22 F400	40089	40 A	AC-23 B	22 kW	4 pieces, M25	150 x 150 x 132
B RS 6+1 30 F400	40090	63 A	AC-23 B	30 kW	2 pieces, M40	200 x 200 x 172
B RS 6+1 45 F400	40091	100 A	AC-23 B	45 kW	2 pieces, M40	200 x 200 x 189
B RS 6+1 55 F400	40092	125 A	AC-23 B	55 kW	2 pieces, M40	200 x 200 x 189
B RS 6+1 75 F400	40093	160 A	AC-23 B	75 kW	without*	400 x 400 x 250

* Removable mounting plate for customised drilling.