

- Isolator switch RS
- 3 pole with auxiliary contact



**RS 3+1 7.5** Ref. no. 06387  
 Plastic casing for surface-mounting. Locking options in position "O OFF" and position "I ON".

**Technical data**  
 Voltage 400 V, 3~, 50/60 Hz  
 Operating current 20 A  
 Capacity AC-23 B, 7,5 kW  
 Prot. category IP65  
 Protect. class II  
 Actuation Rotary actuator  
 Temperature range -25 °C to +60 °C  
 Weight approx. 0.3 kg  
 Casing UV and weather resistant  
 Wiring diagram no. 1088

- 6 pole with auxiliary contact



**RS 6+1**  
 Plastic casing for surface-mounting. Locking options in position "O OFF" and position "I ON".

**Technical data**  
 Voltage 400 V, 3~, 50/60 Hz  
 Prot. category IP65  
 Protect. class II  
 Actuation Rotary actuator  
 Locking options "O OFF" and "I ON"  
 Temperature range -25 °C to +60 °C  
 Casing UV and weather resistant  
 Wiring diagram no. 1088

\*RS 6+1 55: -25 °C to +40 °C.

Type	Ref. no.	Capacity			Cable entry main contact	Size cable entry
<b>For Dahlander winding or <math>\gamma/\Delta</math> start-up</b>						
<b>RS 6+1 7.5</b>	06388	20 A	AC-23 B	7.5 kW	4 pcs	M20
<b>RS 6+1 11</b>	06389	25 A	AC-23 B	11 kW	4 pcs	M25
<b>RS 6+1 15</b>	06390	32 A	AC-23 B	15 kW	4 pcs	M25
<b>RS 6+1 22</b>	06391	50 A	AC-23 B	22 kW	4 pcs	M40/32/25
<b>RS 6+1 37</b>	06392	80 A	AC-23 B	37 kW	4 pcs	M40/50
<b>RS 6+1 45</b>	06393	125 A	AC-23 B	45 kW	4 pcs	M50
<b>RS 6+1 55</b>	06394	125 A	AC-23 B	55 kW	4 pcs	M40/50

- Smoke exhaust isolator switch B RS
- 6 pole with auxiliary contact



**B RS**  
 EN 12101-3 certified smoke spill inspection switch in temperature-time classification F400. Metal casing for surface mounting. Locking options in position "O OFF" and position "I ON".

**Technical data**  
 Voltage 400 V, 3~, 50/60 Hz  
 Prot. category IP65  
 Protect. class II  
 Color RAL 7035  
 Actuation Rotary actuator  
 Temperature-Time classification F400  
 Casing UV and weather resistant  
 Wiring diagram no. 1394

Type	Ref. no.	Capacity		
<b> F400</b>				
<b>B RS 6+1 11 F400</b>	40088	25 A	AC-23 B	11 kW
<b>B RS 6+1 22 F400</b>	40089	40 A	AC-23 B	22 kW
<b>B RS 6+1 30 F400</b>	40090	63 A	AC-23 B	30 kW
<b>B RS 6+1 45 F400</b>	40091	100 A	AC-23 B	45 kW
<b>B RS 6+1 55 F400</b>	40092	125 A	AC-23 B	55 kW