


B AVD 630




Dimensions B AVD 630




Performance curves B AVD 630/4

n=1420 1/min



Accessories for B AVD 630



Certification

The smoke and heat exhaust fans B AVD have been tested according to DIN EN 12101-3.
Certificate of conformity:
F300: 0036-CPR-RG05-03
F400: 0036-CPR-RG05-06

Information

Page
Techn. description 22 f.
Project planning information 10 ff.
Accessory details
Mounting accessories 160 ff.
Attenuators 168
Gas warning systems, switch and control technology 170 ff.

Type	Ref. no.	Speed	Air flow volume (FID)	Motor pow. nom. (output)	No-minal voltage	Power consum. nom.	Pitch angle	Wiring dia-gram	Max. air flow temp. ¹⁾	Dim. B Motor protrusion	Net weight approx.	Pole switch surface-mounted		Anti-vibration mounts NG			
														Pressure		Tensile	
		min ⁻¹	∇ m³/h	kW	V	A	°	No.	+°C	mm	kg	Type	Ref. no.	Type	Ref. no.	Type	Ref. no.
🔥F300 3 phase motor, 50 Hz, protection class IP54																	
B AVD 630/4 0,75 kW F300	02527	1420	14110	0.75	400	1.62	*	776	40 / 300	41	43	EVS-D 001	04594	SDD 1 F	01942	SDZ 1 F	01943
B AVD 630/4 1,1 kW F300	02335	1455	16500	1.1	400	2.35	*	776	40 / 300	59	48	EVS-D 001	04594	SDD 1 F	01942	SDZ 1 F	01943
B AVD 630/4 1,5 kW F300	02336	1450	18700	1.5	400	3.17	*	776	40 / 300	84	52	EVS-D 001	04594	SDD 1 F	01942	SDZ 1 F	01943
B AVD 630/4 2,2 kW F300	02337	1435	21030	2.2	400	4.56	*	776	40 / 300	121	61	EVS-D 001	04594	SDD 1 F	01942	SDZ 1 F	01943
🔥F300 Pole-switching, 2 speed (Dahlander winding ) , 3 phase motor, 50 Hz, protection class IP54																	
B AVD 630/8/4 0,2/0,8 kW F300	02338	690/1415	7210/14420	0.2/0.8	400	0.88/1.99	*	777	40 / 300	41	44	on demand		SDD 1 F	01942	SDZ 1 F	01943
B AVD 630/8/4 0,3/1,2 kW F300	02339	705/1430	8510/17020	0.3/1.2	400	1.29/2.92	*	777	40 / 300	59	49	on demand		SDD 1 F	01942	SDZ 1 F	01943
B AVD 630/8/4 0,4/1,6 kW F300	02528	700/1420	9520/19040	0.4/1.6	400	1.69/3.80	*	777	40 / 300	84	50	on demand		SDD 1 F	01942	SDZ 1 F	01943
B AVD 630/8/4 0,55/2,2 kW F300	02340	700/1430	10410/20810	0.55/2.2	400	2.00/4.84	*	777	40 / 300	121	55	on demand		SDD 1 F	01942	SDZ 1 F	01943
🔥F400 3 phase motor, 50 Hz, protection class IP54																	
B AVD 630/4 0,75 kW F400	02558	1420	14110	0.75	400	1.62	*	776	40 / 400	41	43	EVS-D 001	04594	SDD 1 F	01942	SDZ 1 F	01943
B AVD 630/4 1,1 kW F400	02417	01455	16500	1.1	400	2.35	*	776	40 / 400	59	48	EVS-D 001	04594	SDD 1 F	01942	SDZ 1 F	01943
B AVD 630/4 1,5 kW F400	02418	1450	18700	1.5	400	3.17	*	776	40 / 400	84	52	EVS-D 001	04594	SDD 1 F	01942	SDZ 1 F	01943
B AVD 630/4 2,2 kW F400	02419	1435	20810	2.2	400	4.56	*	776	40 / 400	121	61	EVS-D 001	04594	SDD 1 F	01942	SDZ 1 F	01943
🔥F400 Pole-switching, 2 speed (Dahlander winding ) , 3 phase motor, 50 Hz, protection class IP54																	
B AVD 630/8/4 0,2/0,8 kW F400	02420	690/1415	7210/14420	0.2/0.8	400	0.88/1.99	*	777	40 / 400	41	44	on demand		SDD 1 F	01942	SDZ 1 F	01943
B AVD 630/8/4 0,3/1,2 kW F400	02421	705/1430	8510/17020	0.3/1.2	400	1.29/2.92	*	777	40 / 400	59	49	on demand		SDD 1 F	01942	SDZ 1 F	01943
B AVD 630/8/4 0,4/1,6 kW F400	02559	700/1420	9520/19040	0.4/1.6	400	1.69/3.80	*	777	40 / 400	84	50	on demand		SDD 1 F	01942	SDZ 1 F	01943
B AVD 630/8/4 0,55/2,2 kW F400	02422	700/1430	10410/20810	0.55/2.2	400	2.00/4.84	*	777	40 / 400	121	55	on demand		SDD 1 F	01942	SDZ 1 F	01943

* The flow volume and pressure increase information is required to determine the pitch angle.

¹⁾ For ventilation operation / smoke extraction (one time 120 min. at 300 °C or 120 min. at 400 °C).