



B VAR 710 F600




Dimensions B VAR 710 F600



Performance curves B VAR 710/4 F600



Accessories B VAR 710 F600 Description see page 163 ff.



* Type allocation see table, last column

■ Casing

Duct with flanges on both sides DIN 24155 pt. 3. Welded construction, hot-dip galvanised. Welded guide vane with inner hub for mounting the flange motor, hot-dip galvanised.

■ Impeller

Optimised for high pressure and volume output. Special development with spatially curved hot-dip galvanised steel blades.

■ Motor

Direct through Efficient IE3 three phase motor. Pole-switching

fans with IEC standard motor. Protection class IP55. Insulation class H. External cable with sheathing.

■ Motor protection

All types (except pole-switching) have PTC resistors as standard and must be protected with aa full motor protection device (MSA, Ref. no. 01289). This must be bridged in smoke extraction situation.

■ Installation

Installation in any position. Suitable for installation within and outside of the fire zone.

■ Electrical connection

Standard terminal box (IP54) mounted for installation outside of the fire zone.

■ Safety information

Protection against accidental contact for impeller must be ensured pursuant to DIN EN ISO 13857.

■ Centrifugal cooling air fan

The centrifugal cooling air fan B KLG is a required accessory for ensuring motor cooling. Alternative forced ventilation fan upon request. Minimum cooling air flow rate $V = 565 \text{ m}^3/\text{h}$.

■ Certification

The smoke extraction fans B VARD have been tested according to DIN EN 12101-3. Certificate of performance reliability: F600: 0036-CPR-RG05-02

■ Information Page

Techn. description	84 f.
Project planning information	10 ff.

■ Accessory details

Mounting accessories	163 ff.
Centrif. cooling air fan	162
Gas warning systems, switch and control technology	170 ff.

Type	Ref. no.	Speed	Output free-blowing	Nom. motor power. (output)	Nominal voltage	Power consump- tion	Wiring diagram	max. air flow temp. ¹⁾	Net weight approx.	Smoke exhaust fan control system incl. full motor protection	Anti-vibration mount ²⁾				
											Pressure		Tensile		
		min ⁻¹	Ų m ³ /h	kW	V	A	No.	+°C	kg	Type	Ref. no.	Type	Ref. no.	Type	Ref. no.
 Three phase motor, 50 Hz, protection class IP54															
B VARD 710/4 F600		02853	1470	24460	11.0	400	20.9	776	600	283	EVS-SD 030 04557	SDD 6 01926	SDZ 6 01927		

¹⁾ Smoke extraction (once 120 min.).

²⁾ Types SDZ not permitted for installation within fire zone.