

Accessories

**Smoke detector**

**RMR** Ref. no. 04984  
Smoke detector according to EN 54-7, incl. detector base for the automatic triggering of EVS for smoke detection. Operating voltage 9-33 V DC. Power consum. rest/alarm 30 µA/20 mA. Protection class IP40. Dim. mm Ø 100 x H 44.



**Fire service switch**

**FWS 2** Ref. no. 08255  
Fire service switch with LED display for connection to RDA / TSA. Operating voltage 18 – 30 V DC. Power consum. rest/alarm 2/20 mA. Protection class IP44. Dim. mm 125 x 70.

Accessory:  
Locking cylinder FWS ZY  
Ref. no. 82331.



**Push-button alarm**

**DKM** Ref. no. 04985  
Push-button alarm in limit value technology for manual triggering of EVS by button. Includes reset button and LED indicator for operating state. Operating voltage 20-30 V DC. Protection class IP40. Colour RAL 2011. Dim. mm W 125 x H 125 x D 36



**Safety pressure switch**

**DDB** Ref. no. 82062  
Safety pressure switch for monitoring differential pressures and protection against impermissibly high differential pressure, e.g. in RDA/TSA DDK and TSA. Pressure meas. range 20 to 300 Pa. Capacity switch contact 1.0 (0,4) A, 250 VAC. Protection class IP54. Dim. mm approx. 58 x 104 mm. Installation Wall and ceiling installation.



**Signaltransmitters**

**BLH** Ref. no. 04983  
**BL** Ref. no. 08216  
**WH** Ref. no. 08217  
Flash light siren (BLH), flash light (BL) and siren (WH) as 24 Volt signal transmitters, incl. base. Casing made from impact-resistant plastic, for ceiling and wall installation. Protection class IP65. Dim. mm Ø 93



**Differential pressure sensor**

**DDR** Ref. no. 82061  
Differential pressure sensor in two-wire technology with durable capacitive sensor element. Operating voltage 18 to 30 V DC. Meas. range -100 to +100 Pa. Casing protection class IP65. Dim. mm 106 x 83 x 41 mm. Casing material Polyamide PA 6.6.

Accessories: Connection adapter  
DDR ADPT No. 37525



**Duct smoke detector**

**RMK** Ref. no. 04982  
Duct smoke detector, incl. inlet duct for early detection of fire gases in the outside air inlet at flow speeds of 1 – 20 m/s. Operating current 16-28 V DC. Power consum. rest/alarm 22/11 mA. Protection class IP54. Relay contact potential-free break contact. Dim. mm L 250 x W 135 x H 100.

