

- Isolator switch RS
- 3 pole with auxiliary contact

RS 3+1 7,5





RS 3+1 7,5 Ref. no. 06387
Plastic casing for surface-mounting.
Locking options in position “O OFF”
and position “I ON”.

Technical data	
Voltage	400 V, 3~, 50/60 Hz
Operating current	20 A
Capacity	AC-23 B, 7,5 kW
Prot. category	IP65
Protect. class	II
Actuation	Rotary actuator
Temperature range	-25 °C to +60 °C
Weight approx.	0.3 kg
Casing	UV and weather resistant
Wiring diagram no.	1088

- 6 pole with auxiliary contact

RS 6+1





RS 6+1
Plastic casing for surface-mounting.
Locking options in position “O OFF”
and position “I ON”.

Technical data	
Voltage	400 V, 3~, 50/60 Hz
Prot. category	IP65
Protect. class	II
Actuation	Rotary actuator
Locking options	“O OFF” and “I ON”
Temperature range	-25 °C to +60 °C*
Casing	UV and weather resistant
Wiring diagram no.	1088

*RS 6+1 55: -25 °C to +40 °C.

Type	Ref. no.	Capacity			Cable entry main contact	Size cable entry
For Dahlander winding or ∇/Δ start-up						
RS 6+1 7,5	06388	20 A	AC-23 B	7.5 kW	4 pcs	M20
RS 6+1 11	06389	25 A	AC-23 B	11 kW	4 pcs	M25
RS 6+1 15	06390	32 A	AC-23 B	15 kW	4 pcs	M25
RS 6+1 22	06391	50 A	AC-23 B	22 kW	4 pcs	M40/32/25
RS 6+1 37	06392	80 A	AC-23 B	37 kW	4 pcs	M40/50
RS 6+1 45	06393	125 A	AC-23 B	45 kW	4 pcs	M50
RS 6+1 55	06394	125 A	AC-23 B	55 kW	4 pcs	M40/50

- Smoke exhaust isolator switch B RS
- 6 pole with auxiliary contact

B RS





Illustration similar

B RS
EN 12101-3 certified smoke spill
inspection switch in tempera-
ture-time classification F400 and
F600.
Metal casing for surface mounting.
Locking options in position “O OFF”
and position “I ON”.

Technical data	
Voltage	400 V, 3~, 50/60 Hz
Prot. category	IP65
Protect. class	II
Color	RAL 7035
Actuation	Rotary actuator
Temperature-Time classification	F400/F600
Casing	UV and weather resistant
Wiring diagram no.	1394

Type	Ref. no.	Capacity			Cable inlets for main connectors	Dimensions in mm (WxHxD)
F400						
B RS 6+1 11 F400	40088	25 A	AC-23 B	11 kW	4 pieces, M20, M25	150 x 150 x 132
B RS G 6+1 11 F400*	40961	25 A	AC-23 B	11 kW	4 pieces, M20, M40	200 x 200 x 172
B RS 6+1 22 F400	40089	40 A	AC-23 B	22 kW	4 pieces, M20, M40	200 x 200 x 172
B RS 6+1 30 F400	40090	63 A	AC-23 B	30 kW	4 pieces, M20, M40	200 x 200 x 172
B RS 6+1 45 F400	40091	100 A	AC-23 B	45 kW	4 pieces, M20, M40	200 x 200 x 189
B RS 6+1 55 F400	40092	125 A	AC-23 B	55 kW	4 pieces, M20, M40	200 x 200 x 189
B RS 6+1 75 F400	40093	160 A	AC-23 B	75 kW	without**	400 x 400 x 250
F600						
B RS 6+1 11 F600	40960	25 A	AC-23 A	11 kW	4 pieces, M20, M40	200 x 200 x 172
B RS 6+1 22 F600	40963	40 A	AC-23 B	22 kW	4 pieces, M20, M40	200 x 200 x 172
B RS 6+1 30 F400	40964	63 A	AC-23 B	30 kW	4 pieces, M20, M40	200 x 200 x 172

* With a large casing. ** Removable mounting plate for customised drilling.